

Date: 02 Dec.2022

राजीव गांधी पेट्रोलियम प्रौद्योगिकी संस्थान जायस, अमेठी-229304 उत्तर प्रदेश, भारत

RAJIV GANDHI INSTITUTE OF PETROLEUM TECHNOLOGY JAIS, AMETHI- 229304 UTTAR PRADESH, INDIA

E-TENDER NOTICE

For

"Supply & Installation of 01 no. of "Automatic Rotational Rheometer (Research Grade)"

Rajiv Gandhi Institute of Petroleum Technology (RGIPT), Jais, Amethi, Uttar Pradesh has been established through an Act of the Parliament by the Ministry of Petroleum and Natural Gas (MoPNG), Government of India in 2008.

The Institute has been accorded the eminence of being an Institution of National Importance on the lines of the IITs. The Institute is associating with leading International Universities/ Institutions specializing in Petroleum Technology and Energy.

The Institute invites online bids from authorized Indian suppliers/OEM (Imported equipment/ Indigenous equipment) for the Supply & Installation of 01 no. "Automatic Rotational Rheometer (Research Grade)".

CRITICAL DATE AND INFORMATION

Name of Work	Supply & Installation of 01 no. "Automatic Rotational Rheometer (Research Grade)"		
Tender No.	RGIPT/JAIS/SPG/SS/2022-23/01 Date: 02 Dec.2022		
Date of Issue/publication of Tender Notice	December 5 th 2022, 1700 Hrs		
Bid Document Download Date & Time	December 5 th 2022, 1800 Hrs		
Pre-Bid Meeting Date, Time & Venue (All queries shall be discussed in the Pre- Bid Meeting.)	16 th December 2022, 1500 Hrs AB-1 5 th Floor Conference Room, RGIPT Campus Jain Amethi UP.		
Bid Submission Start Date & Time	December 5 th 2022, 1800 Hrs		
Last Date and time of submission of Bids	December 26 th 2022, 1300 Hrs		
Date and time of opening of Technical Bids	December 27th 2022, 1600 Hrs		
Date and time of opening of Financial Bids	Shall be indicated separately after technical evaluation/ technical bid opening		
	The Director Rajiv Gandhi Institute of Petroleum Technology, Mubarakpur, Mukhtia, Bahadurpur Post: Harbanshganj, Jais, Amethi – 229304		
	Name: Dr. Shivanjali Sharma Email: ssharma@rgipt.ac.in Contact Nos. +91 535 2704520		

Notes:

- Details regarding the tender are available on website of the Institute https://www.rgipt.ac.in and CPP
 Portal.
- 2. Tender document may be downloaded from above mentioned websites. Bidders are therefore, requested to visit the websites regularly to keep themselves updated. Any Addendum/Corrigendum will be displayed on the aforesaid websites only.
- **3.** For submission of e-Bids, bidders are required to get themselves registered with CPP Portal.
- **4.** The HARD COPY of original Bid documents (Only Technical Bid documents) along with the payment proof pertaining to EMD and Tender processing fee to be sent to the Institute at the address indicated below on or before bid opening date/time as mentioned in critical date sheet.
- **5.** Tender documents received in incomplete shape or beyond the stipulated period shall not be entertained under any circumstances. The authority reserves the right to accept or reject any or all tenders without assigning any reason thereof.

6. Earnest Money Deposit (EMD) of Rs.2,10,000/- (Exempted in case of MSME registered, Udyam certificate to be enclosed) in the form of NEFT/Demand Draft, Fixed Deposit Receipt issued by any Nationalized Bank in favour of "Rajiv Gandhi Institute of Petroleum Technology, payable at Jais".

7. Tender Processing Fee (Non-Refundable Rs. 7000/- (Including GST)

Tender fee is exempted for MSME/UAM registered bidders as per Government of India norms

Bank Account Details of the Institute:

Name: Rajiv Gandhi Institute of Petroleum Technology

Bank: Bank of Baroda

Address: RGIPT Campus, Bahadurpur, Jais, Amethi.

Account No. 59480100000001

IFSC Code: BARBOJAICAM (5th Character is ZERO)

ADDRESS OF THE INSTITUTE:

RAJIV GANDHI INSTITUTE OF PETROLEUM TECHNOLOGY, MUBARAKPUR, MUKHTIA MORE, BAHADURPUR, POST: HARBANSHGANJ, JAIS, AMETHI, UTTAR PRADESH 229304,

WEBSITE: WWW.RGIPT.AC.IN

INTRODUCTION

Rajiv Gandhi Institute of Petroleum Technology (RGIPT), Jais, Amethi, Uttar Pradesh has been established through an Act of the Parliament by the Ministry of Petroleum and Natural Gas (MoPNG), Government of India in 2008.

The Institute has been accorded the eminence of being an Institution of National Importance on the lines of the IITs. The Institute is associating with leading International Universities/ Institutions specializing in Petroleum Technology and Energy.

The prime objective of the Institute is to provide education, training, and research to roll out efficient human resources, and to meet the growing requirements of the Petroleum and Energy sector.

The main campus of the Institute is located at Jais, Amethi, Uttar Pradesh and B. Tech., M. Tech., MBA and Ph.D. programmes from there. The Institute has set two centres, namely- Assam Energy Institute (AEI), Sivasagar and Energy Institute, Bengaluru (EIB) to offer Diploma and M. Tech. programmes respectively.

INSTRUCTIONS FOR ONLINE BID SUBMISSION (GUIDELINE FOR BIDDER):

The bidders are required to submit soft copies of their bids electronically on the CPP Portal, using valid Digital Signature Certificates. The instructions given below are meant to assist the bidders in registering on the CPP Portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP Portal.

More information useful for submitting online bids on the CPP Portal may be obtained at: http://eprocure.gov.in/eprocure/app.

1. Registration

- (a) Bidders are required to enroll on the e-Procurement module of the Central Public Procurement Portal (URL: http://eprocure.gov.in/eprocure/app by clicking on the link "Online bidder Enrollment "on the CPP Portal which is free of charge.
- (b) As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for their accounts.
- (c) Bidders are advised to register their valid email address and mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.
- (d) Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by any Certifying Authority recognized by CCA India (e.g. Sift/ nCode / eMudhra etc.), with their profile.
- (e) Only one valid DSC should be registered by a bidder. Please note that the bidders are responsible to ensure that they do not lend their DSC's to others which may lead to misuse.
- (f) Bidder then logs in to the site through the secured log-in by entering their user ID/Password and the password of the DSC/ e-Token.

2. Searching for Tender Documents

- (a) There is various search option built in the CPP Portal, to facilities bidders to search active tenders by several parameters. These parameters could include Tender ID, Organization Name, location, Date Value, etc. there is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as Organization Name, Form of Contract, Location, Date, Other keywords etc. to search for a tender published on the CPP Portal.
- (b) Once the bidders have selected the tenders they are interested in, they may download the required documents/tender schedules. These tenders can be moved to the respective 'my Tenders' folder. This would enable the CPP Portal to intimate the bidders through SMS/e-mail in case there is any corrigendum issued to the tender document.
- (c) The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification/help from the Helpdesk.

3. Preparation of Bids

- (a) Bidder should consider any corrigendum published on the tender document before submitted their bids.
- (b) Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents-including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.
- (c) Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule any generally, they can be in PDF/XLS/RAR/DWF/JPG formats. Bid document may be scanned with 100 dpi with black and white option which helps in reducing size of the scanned document.

(d) To avoid the time and effort required in uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, annual reports, auditor certificate etc.) has been provided to the bidders. Bidders can use "My space" or "Other Important Documents" area available to them to upload such documents. These documents may be directly submitted from the "My space" area while submitting a bid, and need not be upload again and again. This will lead to a reduction in the time required for bid submission process.

4. Submission of Bids

- (a) Bidder should log into the site well in advance for bid submission so that they can upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other issues.
- (b) The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.
- (c) Bidders are required to note that they should necessarily submit their financial bids in the format provided and no other format is acceptable. If the price bid has been given as a standard BOQ format with the tender document, then the same is to be download and to be filled by all the bidders. Bidders are required to download the BoQ file, open it and complete the white colored (unprotected) cells with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it and submit it online, without changing the filename. If the BoQ file is found to be modified by the bidder, the bid will be rejected.
- (d) The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders; opening of bids etc. the bidders should follow this time during bid submission.
- (e) All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorized persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage encryption of sensitive fields is done. Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- (f) The uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- (g) Upon the successful and timely submission of bids (i.e. after Clicking "Freeze Bid Submission" in the portal), the portal will give a successful bid submission message & a bid summary will be displayed with the bid no. and the date & time of submission of the bid with all other relevant details.
- (h) The bid summary has to be printed and kept as an acknowledgement of the submission of the bid, this acknowledgement may be used as an entry pass for any bid opening meetings.

5. Assistance to Bidders

- (a) Any queries relating to the tender document and the terms and conditions contained therein should be addressed to the Tender Inviting Authority for a tender or the relevant contact person indicated in the tender.
- (b) Any queries relating to the process of online bid submission or queries relating to CPP Portal in general may be directed to the 24*7 CPP Portal Helpdesk.

LIST OF DOCUMENTS TO BE UPLOADED

- 1. Bidder should take into account notifications, corrigendum published, if any on the tender document before submitting their bids.
- 2. Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Any deviations from these may lead to rejection of the bid.
- 3. The two-bid system will be followed for this tender. In this system, online offer should be submitted under **TWO-BID System** in two separate e-packets i.e. **"Technical eBid" and "Financial eBid".**

Online Envelope No. 1: "Technical Bid" shall contain (Pdf format only)

S1.	Details of Documents	Documents to be Uploaded	File
No.			Format
	EMD (Earnest Money Deposit): a)The EMD of Rs. 2,10,000/- (Rupees Two Lakhs Ten Thousand only (Exempted in case of MSME registered, certificate to be enclosed) in the form of NEFT/Demand Draft, Fixed Deposit Receipt, Bankers Cheque issued by any Nationalized Bank in favour of "Rajiv Gandhi Institute of Petroleum Technology,payable at Jais". Bank Account Details of the Institute: Name: Rajiv Gandhi Institute of Petroleum Technology Bank: Bank of Baroda Address: RGIPT Campus, Bahadurpur Jais, Amethi. Account No. 59480100000001 IFSC Code: BARBOJAICAM (5th Character is ZERO)	Payment Receipt	.pdf
	b) If any the firms registered with		
	DGS&D, MSME & NSIC are exempted		
	from payment of EMD provided such		
	registration includes the item they are		
	offering which are manufactured by them		
	and not for selling products		
	manufactured by other companies.		
	(Latest Copy must be submitted online		
	for claiming exemption)		
1	Technical Specification Compliance Statement	Upload Technical Specification Compliance Statement on the letter head of the Company inprescribed format as given in Annexure - I	.pdf
2	Manufacturer's Authorization Form	Upload Manufacturer's Authorization Certificate inprescribed format as given in Annexure – 2 or Self Declaration of Manufacturing Unit	.pdf
3	Price Reasonability Certificate	Upload Price Reasonability Certificate on the letter head of the Company in prescribed format as given in Annexure - 3	.pdf
4	Declaration Certificate (Acceptance of terms & conditions of the tender) – In defined format (On the letter head of the Company) - Annexure -4 and	Upload Declaration Certificate(Acceptance of terms & conditions of the tender) & Declaration Sheet on the letterhead of the Company in prescribed format as given in	.pdf

RGIPT, Jais, Amethi reserves the right to reject the bid if any of the above listeddocument/s is

5	Non-Blacklisting Declaration - As on date of submission of the proposal, the	Upload Non-Blacklisting Declaration on Rs. 100.00 non-Judicial	.pdf
	Bidder is neither blacklisted by Central Government/State Government or Instrumentalities thereof nor is any	Stamp Paper in prescribed format as given in Annexure – 5	
	criminal case against the Bidder/ its Partners/ Directors/ Agents pending		
	before any court of law. Non-Blacklisting Certificate on Rs. 100.00		
	non-Judicial Stamp Paper –In defined format - Annexure - 5		
5	Copy of Firm Registration	Upload – Self Attested Copy of	.pdf
		Firm Registration Certificate	
7	Copy of PAN Card & GST No.	Upload – Self Attested Copy of PAN Card & GST No.	.pdf
8	Experience: Bidder should have 3 years'	Upload List of clients & Purchase Orders of	.pdf
	experience in the selling and providing "	Supply of "Automatic Rotational	
	Automatic Rotational Rheometer	Rheometer (Research Grade)" to the	
	(Research Grade) " to reputed Central	mentioned institutions.	
	Government Institutes/Petroleum		
	Engineering Colleges/ Universities/Oil		
	Companies/ Research Institutes/ IITs/		
0	NITs/ IISERs	TT 1 1 1'1 1 1 1 1 1'C' 1' C.1	1.0
9	ISO Certificate: The Bidder or their	Upload valid standard certification of the	.pdf
	OEM should possess any valid standard certification like ISO9001:2008 &	Companylike ISO	
	14001:2004.		
10	Audited Annual Accounts: Bidder should	Upload the Self Attested Copies of last 3	.pdf
10	enclose the copies of last 3 years Audited	years Audited Annual Accounts duly	.par
	Annual Accounts (Balance Sheet) duly	authenticated by Chartered Accountant	
	authenticated by Chartered Accountant	(FY 2020-21, FY 2019-20 & FY 2018-19)	
11	Annual Turnover: Last three years CA	Upload the Self Attested Copy of CA certified	.pdf
	certified turnover certificate (Average	Annual Turnover Certificate (FY 2020-21, FY	·par
	Turnover of last three years should be at least Rs. 35.00 lakhs	2019-20 & FY 2018-19)	
	(Rupees Thirty Five Lakhs only)	,	
12	Last 3 year Income Tax Return (ITR)	Upload the Self Attested Copy oflast 3 year	.pdf
		Income Tax Return (ITR) – (FY 2020-21, FY	_
		2019-20 & FY 2018-19)	
13	EMD Exemption -In case of exemption of	Upload Self Attested Copy of MSME or any	.pdf
	EMD, the scanned copy of the document in support of exemption will have to be	other valid certificate for EMD exemption	
	uploaded by the bidder during bid		
	submission		
14	MOST IMPORTANT: Document related to	Upload Self Attested Copies of 3 installations in Academic and R&D National	.pdf
	prior installation and service – At least 3	Organizations, Central and State	
	Academic and R&D National	Government Departments/ Institutions/	
	Organizations, Central and State	PSUin the last 3 years. – Annexure - 6	
	Government Departments/		
	Institutions/PSU in the last 3 years.		
15	Any other relevant document		.pdf
	(e.g., Item brochure, etc.)		

not submitted.

- 1. The Financial Bid should be filled properly in the .xls/BoQ uploaded in the CPP portal.
- 2. Financial bids of the technically qualified bidders only will be opened, through CPP portal.
- 3. Financial bids must be offered in the format attached as per Specimen BoQ and tender document.
- 4. In case of any mistake or error in calculations or any discrepancy in the price quoted in word and figures, the LOWEST amount will be considered for comparison. If this lowest price is not acceptable to the bidder, their bid will be rejected. In this case, RGIPT, Jais, Amethi reserves the right to forfeit their EMD.

SECTION-II - INSTRUCTIONS TO THE BIDDERS (ITB)

Tenderers are advised to follow the instructions provided in the **Instructions to theBidders** for the e-Submission of the bids online.

1. Location of Supply & Installation of Equipment & Warranty Services:

Rajiv Gandhi Institute of Petroleum Technology, Mubarakpur, Mukhetia More, Bahadurpur, Post: Harbanshganj, Jais, Amethi – 229304, Uttar Pradesh.

2. All the items covered in the Schedule of Requirements must be supplied within 16 weeks from the date of opening of LC (For Foreign Manufacturer) & 16 weeks from the date of placement of purchase order (For Indian Manufacturer). And after receipt of equipment, the same must be installed within a month's time.

3. Amendment to Bidding Documents:

- a) At any time prior to the deadline for submission of bids, RGIPT, Jais, Amethi may, for any reason, whether on its own initiative or in response to the clarification request by a prospective bidder, modify the bid document.
- b) The amendments to the tender documents, if any, will be notified by release of Corrigendum Notice on institute website against this tender. The amendments/modifications will be binding on the bidders.
- c) RGIPT, Jais, Amethi at its discretion may extend the deadline for the submission of bids if it thinks necessary to do so or if the bid document undergoes changes during the bidding period, in order to give prospective bidders time to take into consideration the amendments while preparing their bids.

4. Preparation of Bids

Bidder should avoid, as far as possible, corrections, overwriting, erasures or postscripts in the bid documents. In case however, any corrections, overwriting, erasures or postscripts have to be made in the bids, they should be supported by dated signatures of the same authorized person signing the bid documents. However, bidder shall not be entitled to amend/add/delete/correct the clauses mentioned in the entire tender document.

5. Period of validity of bids:

- a) Bids shall be valid for minimum 180 days from the date of submission. A bid valid for a shorter period shall stand rejected.
- b) RGIPT, Jais, Amethi may ask for the bidder's consent to extend the period of validity. Such request and the response shall be made in writing only. The bidder is free not to accept such request without forfeiting the EMD. A bidder agreeing to the request for extension will not be permitted to modify his bid.

6. Deadline for Submission of Bids - online only:

- a) The Bid documents shall be neatly arranged. They should not contain any terms and conditions, printed or otherwise, which are not applicable to the Bid. **The conditional** bid will be summarily rejected.
- b) Bids must be received by RGIPT, Jais, Amethi before the due date and time at the address specified in the tender document.
- c) RGIPT, Jais, Amethi may extend this deadline for submission of bids by amending the bid documents and the same shall be suitably notified on its website.
- d) RGIPT, Jais, Amethi shall not be responsible and liable for **the delay in receiving the bid** for whatsoever reason.

7. Institute's Right to amend/cancel:

- a) RGIPT, Jais, Amethi reserves the right to amend the eligibility criteria, commercial terms & conditions, Scope of Supply, technical specifications etc.
- b) RGIPT, Jais, Amethi reserves the right to cancel the entire tender without assigning any reasons thereof.

8. Corrupt or Fraudulent Practices:

- a) It is expected that the bidders who wish to bid for this tender have highest standards of ethics.
- b) RGIPT, Jais, Amethi will reject bid if it determines that the bidder recommended for award has engaged in corrupt or fraudulent practices while competing for this contract.
- c) RGIPT, Jais, Amethi may declare a vendor ineligible, either indefinitely or for a stated duration, to be awarded a contract if it at any time determines that the vendor has engaged in corrupt and fraudulent practices during the award / execution of contract.

9. <u>Interpretation of the clauses in the Tender Document/ Contract Document</u>

a) In case of any ambiguity/ dispute in the interpretation of any of the clauses in this Tender Document, the interpretation of the clauses by Director, RGIPT, Jais, Amethi shall be final and binding on all parties.

Chairman

SECTION III- ELIGIBILITY AND QUALIFICATION CRITERIA

The following documents should be submitted for eligibility and qualification in technicalbid-

S1. No.	Description
	EMD (Earnest Money Deposit): a)The EMD of Rs. 2,10,000/- (Rupees Two Lakhs Ten Thousand only (Exempted in case of MSME registered, certificate to be enclosed) in the form of NEFT/Demand Draft, Fixed Deposit Receipt, Bankers Cheque issued by any Nationalized Bank in favour of "Rajiv Gandhi Institute of Petroleum Technology, payable at Jais". Bank Account Details of the Institute: Name: Rajiv Gandhi Institute of Petroleum Technology Bank: Bank of Baroda Address: RGIPT Campus, Bahadurpur Jais, Amethi. Account No. 59480100000001 IFSC Code: BARBOJAICAM (5th Character is ZERO)
	b) If any the firms registered with DGS&D, MSME & NSIC are exempted from payment of EMD provided such registration includes the item they are offering which are manufactured by them and not for selling products manufactured by other companies. (Latest Copy must be submitted online for claiming exemption)
1	Technical Specification Compliance Statement - (On the letter head of the Company) - Annexure -1
2	Manufacturer's Authorization Form – In defined format OR Self Declaration of Manufacturing Unit – Annexure – 2
3	Price Reasonability Certificate – In defined format (On the letter head of theCompany)- Annexure – 3
4	Declaration Certificate (Acceptance of terms & conditions of the tender) – In defined format (On the letter head of the Company) – Annexure – 4 and Declaration Sheet as per Annexure – 4A .
5	As on date of submission of the proposal, the Bidder is neither blacklisted by Central Government/ State Government or Instrumentalities thereof nor is any criminal case against the Bidder/ its Partners/ Directors/ Agents pending before any court of law. Non-Blacklisting Certificate on Rs.100.00 non-Judicial Stamp Paper – In defined format – Annexure – 5
6	Copy of Firm Registration
7	Copy of PAN Card & GST No.
8	Bidder should have 3 years' experience in the selling and providing "Automatic Rotational Rheometer (Research Grade)" to reputed Central Government Institutes/Petroleum Engineering Colleges/ Universities/ Oil Companies/ Research Institutes/ IITs/ NITs/ IISERs (Self Declaration) – List of Clients & Purchase Orders of "Automatic Rotational Rheometer (Research Grade)" to be submitted.
9	The Bidder or their OEM should possess any valid standard certification like ISO9001:2008 & 14001:2004.
10	Bidder should enclose the copies of last 3 years Audited Annual Accounts (Balance Sheet and Profit & Loss A/c) duly authenticated by CharteredAccountant(FY 2020-21, FY 2019-20 & FY 2018-19)
11	Last three years CA certified turnover certificate (<u>Average Turnover of last</u> three years should be at least Rs. 35.00 lakhs (Rupees Thirty Five Lakhs only) (FY 2020-21, FY 2019-20 & FY 2018-19)
12	Last 3 year Income Tax Return (ITR) (FY 2020-21, FY 2019-20 & FY2018-19)
13	In case of exemption of EMD, the scanned copy of the document in support of exemption will have to be uploaded by the bidder during bid submission
14	MOST IMPORTANT: Document related to prior installation and service – Atleast 3 Academic and R&D National Organizations, Central and State Government Departments/Institutions/PSU in the last 3 years. Annexure – 6

MOST IMPORTANT: PLEASE DON'T ADD OR UPLOAD ANY ANNEXURE OF PRICE IN TECHNO-COMMERICAL BID DOCUMENTS, OTHERWISE YOUR BIDWILL BE REJECTED.

SECTION IV: GENERAL CONDITIONS OF CONTRACT

1. Tender filling up and submission

- a. Tender offer must refer to the letter/Notice inviting the Tender.
- b. The bid should be uploaded online mentioning "Supply & Installation of 01 no.
 Automatic Rotational Rheometer (Research Grade) to Rajiv Gandhi Institute of Petroleum Technology, Jais, Amethi.
- c. Bids must be submitted online against above-mentioned tender.
- d. The rates quoted should include all the components mentioned in the tender and should be valid for at- least 180 days from the date of opening of the bids. The rates must be quoted both in figures and words and overwriting should be avoided. However, all cuttings/corrections must be duly authenticated.
- e. The bid submitted must not contain any ambiguity. Any such ambiguity in the quote submitted shall make it liable for rejection.
- f. The tender document is not transferable.
- g. No amendment to the bid in any form by the bidder will be permitted after opening of the tender. No conditional offers shall be accepted.
- h. Submission of bid will bind the bidder to the acceptance of all conditions specified in the tender document.
- i. Canvassing in any form is forbidden and will be a criterion for disqualification.

2. **EMD (Earnest Money Deposit):**

EMD (Earnest Money Deposit):

a)The EMD of Rs. 2,10,000/- (Rupees Two Lakhs Ten Thousand only (Exempted in case of MSME registered, certificate to be enclosed) in the form of NEFT/Demand Draft, Fixed Deposit Receipt, Bankers Cheque issued by any Nationalized Bank in favour of "Rajiv Gandhi Institute of Petroleum Technology, payable at Jais". Bank Account Details of the Institute: Name: Rajiv Gandhi Institute of Petroleum Technology

Bank: Bank of Baroda Address: RGIPT Campus, Bahadurpur Jais, Amethi.

Account No. 59480100000001

IFSC Code: BARBOJAICAM (5th Character is ZERO)

- b) If any the firms registered with DGS&D, MSME & NSIC are exempted from payment of EMD provided such registration includes the item they are offering which are manufactured by them and not for selling products manufactured by other companies. (Latest Copy must be submitted online for claiming exemption)
- 3. Performance Security: The successful bidder will provide "Performance Security" for an amount of 3% of the contract value in the form of valid Account payee Demand Draft/FDR from any of the scheduled bank favouring "Rajiv Gandhi Institute of Petroleum Technology" payable at RGIPT, Jais, Amethi Campus Branch. Performance security should remain valid at least for a period of 60 days beyond the date of completion of all contractual obligations of supplier (Total Period of FDR/Demand Draft Warranty Period plus 60 days). Thereafter the security will be returned, provided there is no defect in the equipment supplied. (As per notification no. RGIPT/Jais/Admin/46/2021)

The performance security should remain valid at least for a period of 60 days of beyond the date of completion of all contractual obligations of supplier. (As per notification no. RGIPT/Jais/Admin/845/2020)

- 4. **<u>Bid Validity</u>**: The bid must be valid for 180 days from the date of submission.
- 5. **Price bid submission**: In case of imported equipment, price (quote) shall be in two parts (a) CIF (Cost, Insurance, Freight) price upto Airport in Foreign currency, and (b) from Airport to destination (RGIPT, Jais, Amethi) in Indian currency. The components covered in this schedule consist of custom duty; custom clearance charges; freight charges, & Installation and training charges etc, which will be reimbursed in Indian currency to the Indian counterpart as per actual (Up to the maximum limit quoted in the bid), on submission of the original supporting bills duly certified and stamped by the Chairman Purchase Committee.

6. Technical Bid Evaluation Criteria:

The Bid shall be evaluated as per rule-192 of GFR, 2017 by following the Quality and Cost Based Selection (QCBS) system.

Phase-I: Technical Evaluation

Technical evaluation (Marks based evaluation) will be done based on the information given by technical bid submitted by the bidders.

Bid containing partial, incomplete, uncleared and irrelevant information will be summarily rejected. Technical declaration must be supported with relevant documents. Discrepancy in relevant supporting documents and technical compliance sheet shall lead to rejection of the technical bids.

Phase-II: Financial Evaluation

- a) Financial bids of only technically qualified bidders shall be opened.
- b) Financial evaluation is purely done on the total financial implication.
- c) Any irrelevant, unreasonable assets rate quotes will be summarily rejected.

Evaluation of Technical and Financial Bids:

- a) Selection of the successful bidder shall be based on techno-commercial combined score. Weightage of 60% and 40% shall be given to technical criteria and financial bid respectively. Minimum technical score required is 70 marks out of 100 marks with qualification in each criteria. Any bidder scoring technical score of less than 70 marks will not be considered for financial evaluation.
- b) Technical Bids shall be opened first and evaluated for the bidder's eligibility criteria, bid completeness, bid conformity, bid responsiveness, before opening Financial Bid.
- c) Techno-Commercial Score: The final score shall be calculated for all technically qualified bidders using the formula: [(Technical score/ Highest Technical Score) x 60%] + [(Minimum Financial quote/ quoted price of the Bidder) x 40%].
- d) The bidder with the highest Overall or Combined Score as computed above will be considered for engagement.
- e) The decision of RGIPT shall be final and binding on all the Bidders to this document. RGIPT reserves the right to accept or reject an offer without assigning any reason whatsoever.
- f) The financial bids shall be opened for the firms getting minimum 70 marks in technical
- g) In case of a tie, preference will be given to the bidder who have secured higher technical
- 7. In order to understand profile of the firm and to have a clear understanding of the areas in which firm is having requisite expertise, RGIPT may at its absolute discretion invite one or more or all the bidders for further presentation.

8. Special Instructions:

- i) Non-receipt of quote in foreign currency for imported equipment may lead to the rejection of their bid without assigning any reason thereof.
- ii) RGIPT shall provide custom/excise duty exemption certificate and GST exemption certificate on request by the bidder.
- iii) RGIPT, Jais, Amethi avails custom duty exemption in terms of Government Notification No. 51/96-Customs dated 23 July, 1996, and Central Excise Duty Exemption in terms of Government Notification No. 10/97-Central Excise dated 01 March, 1997, as amended time to time.
- iv) RGIPT, Jais, Amethi avails GST concession under notification No. 47/2017 Integrated tax (rate) dated 14 November 2017, as amended time to time.

9. Payment terms:

i) <u>In Indian Currency Payment Terms</u> - 80% payment will be released against successful supply of equipment at site i.e Rajiv Gandhi Institute of Petroleum Technology, Jais, Amethi and balance 20% after installation & commissioning of the equipment and subject to submission of original Bill/ Invoice as certified by the Chairman, purchase committee.

- ii) In Foreign Currency payment Terms 80% payment by an irrevocable letter of credit favoring Principal Company and for compliance of payment term, two weeks prior to dispatch of the equipment on submission of letter from Principal Company confirming that the equipment is ready for dispatch, receipt of documents without any discrepancies & Copy of 110% Insurance and balance 20% will be paid after satisfactory installation and commissioning as certified by the, purchase committee.
- iii) Reimbursement of Expenses in Indian Rupees: The Institute will reimburse the expenses in Indian Rupees related to custom duty, custom clearance charges, transportation charges upto RGIPT, Jais, Amethi to the Indian Counterpart after the installation and commissioning of equipment at site (Upto maximum limit defined in the bid) i.e Rajiv Gandhi Institute of Petroleum Technology, Jais, Amethi 229304 and subject to submission of original bill certified by the Indenter.
- 10. **Clearance and delivery**: On arrival of shipment/consignment, the supplier is required to arrange custom clearance and transportation of the consignment up to RGIPT, Jais, Amethi premises. The Tenderer/ bidder will do all types of clearance work and formalities to deliver/provide the equipment at the site of installation. The expenses incurred will be reimbursed on actual basis not exceeding the quoted amount. Institute will provide all types of documentary support including Customs Duty exemption certificate. The custom duty, custom clearance charges, transportation charges etc. will be reimbursed in Indian Rupees on subject of submission of documentary proof. This may be included in your quotation as a separate item. Principals will themselves have to procure any requisite permission from the Govt. of country of origin of equipment.
- 11. Part Shipment not allowed: Part Shipment will NOT be allowed.
- 12. **Insurance**: For delivery of goods at the purchaser's premises, the insurance shall be obtained by the supplier in an amount equal to 110% of the value of the goods from "warehouse to warehouse" (final destinations) on "All Risks" basis including War Risks and Strikes. The insurance shall be valid for a period of not less than 3 months after installation and commissioning. If orders placed on CIF/CIP basis, the insurance should be up to RGIPT, Jais, Amethi.
- 13. **Bank Charges**: All the bank charges within India will be borne by the Institute and outside India will be borne by the Supplier.
- 14. **Site Preparation**: The supplier shall inform to the Institute about the site preparation, if any, needed for the installation of equipment, immediately after the receipt of the purchase order. The supplier must provide complete details regarding space and all the other infrastructural requirements needed for the equipment, which the Institute should arrange before the arrival of the equipment to ensure its timely installation and smooth operation thereafter. The supplier shall visit the Institute and see the site where the equipment is to be installed and may offer his advice and render assistance to the Institute in the preparation of the site and other pre-installation requirements.
- 15. **Resolution of Disputes**: The dispute resolution mechanism to be applied pursuant shall be as follows:
 - i. In case of Dispute or difference arising between the Purchaser and a domestic supplier relating to any matter arising out of or connected with this agreement, such disputes or difference shall be settled in accordance with the Indian Arbitration & Conciliation Act, 1996, the rules there under and any statutory modifications or re-enactments thereof shall apply to the arbitration proceedings. The dispute shall be referred to The Director, Rajiv Gandhi Institute of Petroleum Technology, Jais, Amethi and if he is unable or unwilling to act, to the sole arbitration of some other person appointed by him willing to act as such Arbitrator. The award of the arbitrator so appointed shall be final, conclusive and binding on all parties to this order.
 - ii. In the case of a dispute between the purchaser and a Foreign Supplier, the dispute shall be settled by arbitration in accordance with provision of sub-clause (a) above. But if this is not acceptable to the supplier then the dispute shall be settled in accordance with provisions of UNCITRAL (United Nations Commission on International Trade Law) Arbitration Rules.
 - The venue of the arbitration shall be the place from where the order is issued.
- 16. Live working product Demo of same or similar item is necessary (at the cost of bidder) for all the bidders, if asked for, within the ONE week of opening the technical bid.

- 17. **Printed Conditions of the Company Not Acceptable to the Institute**: RGIPT does not accept the printed conditions of any Tenderer. It will be ignored without any reference; hence tenderers should withdraw such printed conditions if they have any. RGIPT shall accept only unconditional tender.
- 18. <u>Technical Deviations Sole discretion of RGIPT for consideration</u>: If technical deviations furnished by the Tenderer are not agreeable to RGIPT, the offers may be ignored. However it will be solely at discretion of RGIPT to consider the technical deviations OR not for considering the Tenderer. No correspondences of the Tenderer will be entertained in this matter.
- 19. **Price Validity:** The price quoted by the bidder shall remain valid till the supply is completed. During the tenure of the supply period, no price increase will be considered, except for change in statutory levies imposed by Centre Govt. / state Govt. or Local authorities.
- 20. **Warranty:** As specified in the Technical Specification.
- 21. **Delivery:** The timely delivery of "Automatic Rotational Rheometer (Research Grade)" is the essence of contract. The supply should be completed with the specified delivery. Delivery shall be completed must be supplied within 16 weeks from the date of opening of LC (For Foreign Manufacturer) & 12 weeks from the date of placement of purchase order (For Indian Manufacturer).

22. Bid Acceptance and Rejection:

- a. RGIPT reserves the right to reject the bid without assigning any reason what so ever.
- b. RGIPT does not bind itself to accept the lowest or any quotation and reserves the right to reject any or all without assigning any reason.
- 23. Late Receipt of Bids: No bids will be accepted or considered after the due date and time.
- 24. **Liquidity Damage Clause:** RGIPT, Jais reserves the right to levy penalty @ of 0.5 % of order value per week of delay in supply and /or installation, beyond the schedule as mentioned in this tender document subject to maximum of 5% of the order value. RGIPT, Jais reserves the right to cancel the order in case the delay is more than 06 weeks. The delay in delivery and/or installation not attributed to supplier viz. delay in site preparation, delay in submission of required documents etc. and the conditions arising out of Force Majeure will not be considered for the purpose of calculating penalties.

25. **Ship to**

Dr. Shivanjali Sharma Project In-charge Rajiv Gandhi Institute of Petroleum TechnologyGround Floor, Administrative Building Mubarakpur, Mukhetia More, Bahdupur, POST: Harbanshganj, Jais, Amethi – 229304 Uttar Pradesh

- 26. **Withdrawal of Tender**: The Institute reserves the right to withdraw the tender at any stage of tendering process with the approval of the Competent Authority.
- 27. **Replacements of Goods Broken, Damaged or Short:** If whole or part of the goods/ equipment supplied against the order is found defective/non-functional or without specification the supplier will have to replace the defective goods/equipment to make equipment operational within a reasonable time (not exceeding two months from the date of intimation to the supplier or the Indian Agent), failure to which the supplier will have to refund the full cost of the equipment including freight, Insurance etc.
- 28. **Force Majeure:** RGIPT, Jais may consider relaxing the penalty and delivery requirements, as specified in this document, if and to the extent that, the delay in performance or other failure to perform its obligations under the contract is the result of a Force Majeure. Force Majeure is defined as an event of effect that cannot reasonably be anticipated such as acts of God (like earthquakes, floods, storms etc.), acts of states / state agencies, the direct and indirect consequences of wars (declared or undeclared), hostilities, national emergencies, civil commotion and strikes at successful Bidder's premises or any other act beyond control of the bidder.

- 29. **Arbitration:** All disputes/clams of any kind arising out of supply, commissioning, acceptance, warranty maintenance etc. under this Contract, shall be referred by either party (RGIPT, Jais or the bidder) after issuance of 30 days' notice in writing to the other party clearly mentioning the nature of dispute to the Sole Arbitrator appointed by RGIPT, Jais. The arbitration proceedings shall be conducting in English and as per the provisions of Indian Arbitration and Conciliation Act, 1996. The decision of the Arbitrator shall be final and binding on both the parties.
- 30. **Jurisdiction**: The disputes, legal matters, court matters, if any shall be subject to Raebareli/ Amethi jurisdiction only.
- 31. A bid submitted with false information will not only be rejected but the vendor may also be debarred for participation in future tendering processes.
- 32. Authorized representative may choose to be present at the time of opening of quotation at their own cost.
- 33. Only one PRICE BID should be submitted for the above equipment. A bidder who submits more than one PRICE BID, shall be disqualified and considered non-responsive.

Chairman, Purchase Committee

Automatic Rotational Rheometer (Research Grade) for high-precision rheology and viscoelastic measurements of carbonated water (**carbon dioxide pressurization facility at above 2000 psi is essential**), high & low viscosity dispersions/complex fluids (polymers, drilling fluids, lubricants, oils, grease, etc) and building construction materials (cement, concrete, plaster, etc.)

Technical Specifications

- 1. The equipment should be **modular** (allowing different accessory assemblies to connect) and should facilitate easy sampling handling.
- 2. The Rheometer should have the capability to perform Rheological Studies in the following modes (measurement types):
 - a. Rotational.
 - b. Oscillatory.
 - c. Transient.
- 3. Equipment should have an air, nitrogen, and carbon dioxide pressurization system (compressor unit should be included) for pressurized rheological measurement.
- 4. The equipment should accompany a high-speed (1 HP or better) compressor with a drain valve.
- 5. **Measuring Head Type:** Direct current synchronous motor with permanent magnets on its rotor or drag cup motor.
- 6. Motor Bearing Type
 7. Gap Control (standard)
 2. Air bearing/magnetic bearing.
 3. Automatic gap compensation.
- 8. Torque Range
 - a. Minimum Torque (rotation)
 b. Minimum Torque (oscillation)
 c. Maximum Torque
 d. Torque Resolution
 1 nNm or better.
 20.6 nNm or better.
 200 mNm or better.
 0.007 μNm or better.
- 9. Angular velocity
 - a. Minimum : 0 rad/sec.
 - b. Maximum : 300 rad/sec or better.
- 10. Frequency
 - a. Minimum : 10E-7 rad/sec or better.
 b. Maximum : 628 rad/sec or better.
- 11. Normal Force
 - a. Maximum : 50 N or better.b. Resolution : 0.5 N or better.
- 12. **Strain/Displacement Sensor** : High-resolution optical encoder.
 13. **Modes** : Direct strain & stress amplitudes.
- 14. The Rheometer should have the following functionalities: employ a **Quick Fit concept** of connecting tools without any threading or special fixtures. The Rheometer should have to capability to wirelessly identify the connected tools. The Tools should be supported with an **Automatic Locking system** to allow ease of Sample loading & trimming.
- 15. The **Rheology Software** should have built-in templates pre-programmed for all materials, and the software must be compatible with the Windows 10/11 or Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like
 - a. Viscosity Curve across variable time, temperature, shear rate, and shear stress.
 - b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress.
 - c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region).
 - d. Elastic Modulus, Loss Modulus, Complex Modulus and tan d vs time, temperature, frequency, strain, and stress in shear and linear modes.
 - e. Creep Compliance as a function of time at different Temperatures in single or multiple creep zones.
 - f. Modeling & curve fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models.
- 16. The following assemblies should be provided with corresponding utilities:
 - a. **Peltier Plate Device** (0 °C to 180 °C or better)
 - i. Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set.

- ii. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm –
- iii. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) 1 set.
- iv. The geometries should have stainless steel shafts which can connect with system.

b. Pressure Cell Assembly

- i. It should allow pressurization with air, nitrogen and carbon dioxide (essential).
- ii. It should include a **hybrid pressurization pump** for nitrogen, air, and carbon dioxide pressurization.
- iii. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities.
- iv. The cell should be preferably made of titanium for anti-corrosion while using carbonated fluids.
- v. Double gap measuring geometry (made of titanium) for low viscous samples 1 set.
- vi. The assembly should accompany a temperature control device for electrical heating between 0 °C to 180 °C or better with the necessary utilities and a circulator.
- vii. A minimum pressure of 150 bar is essential; however, a pressure of up to **400 bar or better is desirable** with a pressure sensor for a complete range.

c. Building Material Cell (BMC)

- i. The BMC should be able to handle paste-like material with bigger particles (e.g., cement slurry) and abrasive materials (particle size up to 5mm).
- ii. It should include a suitable sample cup, a stirrer (for abrasive materials), and a cage that prevents slippage of the cup, which should also be easy to clean.
- iii. The approximate sample volume should be 400ml.
- iv. The assembly should have an air-cooled Peltier Temperature control (0 $^{\circ}\mathrm{C}$ to 80 $^{\circ}\mathrm{C}$ or better)
- v. Air dryer and air filtration unit to separate oil, fine particles, etc.
- 17. The system should be upgradable to powder rheology, tribology & humidity attachments
- 18. The system should be offered with a suitable & branded Windows 10/Macintosh-based or higher operating system-based **PC workstation** with licensed Microsoft Office, at least Intel i7 11th generation/AMD Ryzen 7 processor, high-definition webcam with in-built microphone, 500GB SSD, 1 TB HDD, 16GB RAM, 27" LED Display, external CD/DVD drive, Bluetooth 5.0 or better, WiFi, 4GB graphics card.
- 19. A branded air conditioner (AC) for standard temperature and humidity control should be provided to ensure better functioning of the equipment.
- 20. The OEM should facilitate on-site installation with training.
- 21. The OEM should provide 3 years on-site warranty with spares with additional 3 years post-warranty Annual Maintenance Support.

Place:	
Date:	Signature and seal of the Manufacturer/

Technical Specifications Compliance Statement of "Supply & Installation of 01 no.

Automatic Rotational Rheometer (Research Grade)" should be submitted as per format given in Annexure – I (On the Company's Letter Head)

TECHNICAL SPECIFICATIONS COMPLIANCE STATEMENT

Online Tenders from authorized Indian suppliers/OEM (Imported equipment/ Indigenous equipment) for supply & Installation of **01 no. of Automatic Rotational Rheometer"** are invited by the Rajiv Gandhi Institute of Petroleum Technology, Amethi- 229304 in **Two-Part Bid System** as per specifications mentioned below:

Please mention the brand and model no. & name of the equipment

Please mention the brand and model no. & name of the Technical Specifications			Bidder's Specification	Compliance/ Deviation
1		-	Bluder's Specification	Compliance/ Deviation
1.	Automatic	• The equipment should		
	Rotational Rheometer	be modular (allowing different accessory		
	Kileometer	5		
		assemblies to connect) and should facilitate		
		easy sampling		
		handling.		
		/D1 D1 , 1 11		
		The Rheometer should		
		have the capability to		
		perform Rheological		
		Studies in the following		
		modes (measurement		
		types):		
		o Rotational.		
		o Oscillatory.		
		o Transient.		
		• Equipment should		
		have an air, nitrogen, and carbon dioxide		
		pressurization system (compressor unit		
		(compressor unit should be included)		
		for pressurized		
		rheological		
		measurement.		
		measurement.		
		The equipment should		
		The equipment should		
		accompany a high-		
		speed (1 HP or better) compressor with a		
		compressor with a drain valve.		
		drain vaive.		
		Measuring Head		
		Type: Direct current		
		synchronous motor		
		with permanent		
		magnets on its rotor or		
		drag cup motor.		
		Motor Bearing Type		
		:		
		Air bearing/magnetic		
		bearing.		
		• Gap Control		
		(standard) :		
		Automatic gap		
		compensation.		
		Torque Range		
		o Minimum Torque		
		(rotation) : 1		
		nNm or better.		
		o Minimum Torque		
		(oscillation): 0.6		
		nNm or better.		
		o Maximum Torque : 200		
<u></u>		mNm or better.		

o Torque Resolution	
:	
0.007 μNm or	
better.	
• Frequency	
o Minimum:10E-	
⁷ rad/sec or	
better.	
o Maximum:	
628 rad/sec or	
better.	
Strain/Displacement	
Sensor : High-	
resolution optical	
encoder.	
22. Modes: Direct strain &	
stress amplitudes.	
The Rheometer should have	
the following functionalities:	
employ a Quick Fit concept of	
connecting tools without any	
threading or special fixtures.	
The Rheometer should have to	
capability to wirelessly identify	
the connected tools. The Tools	
should be supported with an	
Automatic Locking system to	
allow ease of Sample loading &	
trimming	
1. The Rheology Software	
should have built-in	
templates pre-programmed	
for all materials, and the	
software must be	
compatible with the	
Windows 10/11 or	
Windows 10/11 or	
Macintosh operating	
Macintosh operating system. The software	
Macintosh operating system. The software should be pre-programmed	
Macintosh operating system. The software should be pre-programmed for all types of materials	
Macintosh operating system. The software should be pre-programmed	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress.	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress.	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress.	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs.	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region).	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, Complex Modulus	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, Complex Modulus and tan d vs time,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, Complex Modulus and tan d vs time, temperature, temperature,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, and tan d vs time, temperature, frequency, strain, and tan d vs time, temperature, frequency, strain,	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, Complex Modulus and tan d vs time, temperature, frequency, strain, and stress in shear	
Macintosh operating system. The software should be pre-programmed for all types of materials and testing protocols for all types of rheology variables to obtain data profiles like a. Viscosity Curve across variable time, temperature, shear rate, and shear stress. b. Complex viscometric measurements across variable time, temperature, frequency, strain, and stress. c. Shear Stress vs. Shear Stress vs. Shear Strain to identify the samples' LVER (Linear Viscoelastic Region). d. Elastic Modulus, Loss Modulus, and tan d vs time, temperature, frequency, strain, and tan d vs time, temperature, frequency, strain,	Page 21 o

are function of temperatures in single or multiple creep zones. f. Modeling & curve fitting facility to classify material behaviour by various rheological particular behaviour by various rheological particular behaviour beh		
time at different Temperatures in single or multiple creep zones. f. Modeling & curve fitting facility to define the second of the second of the second behaviour by various threlogical models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corrected to the second of t	e. Creep Compliance	
Temperatures in single or multiple creep zones. I. Modeling & curve fitting facility to classify material behaviour objects of the control o	as a function of	
Temperatures in single or multiple creep zones. I. Modeling & curve fitting facility to classify material behaviour objects of the control o	time at different	
single or multiple creep zones. f. Modeling, & curve fitting facility to classify material behaviour by various rheological models. flow, and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0° Ct to 180 °C or better) Petiter temperature control-enabled plate for heating and control-enabled plate for heating and control-enabled plate Geometry with measuring plate diameter (stainless steel) plate diameter (stainless steel) of 50-60mm - 1 ser. Oome Plate Geometry with measuring cone diameter 25mm with 21 and 22 and 23 and 24 and 24 and 25 a		
f. Modeling & curve fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Patier Plate Device (0 °C to 180 °C or better) Pettier temperature control-chabled plate for heating and cooling of the samples with a screw-on plate holder 1 set. Parallel Cocumely with a screw-on plate holder 1 set. Parallel Geometry with diameter (stainless steel) of 50-60mm - 1 set. Cone Plate Geometry with measuring cone diameter 2 Som with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel should have stainless steel should have stainless steel should have stainless steel should have stainless and carbon dioxide (essential). Pressure Cell The should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should expressuriation appressure head with the pressurs upply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
f. Modeling & curve fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Patier Plate Device (0 °C to 180 °C or better) Pettier temperature control-chabled plate for heating and cooling of the samples with a screw-on plate holder 1 set. Parallel Cocumely with a screw-on plate holder 1 set. Parallel Geometry with diameter (stainless steel) of 50-60mm - 1 set. Cone Plate Geometry with measuring cone diameter 2 Som with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel should have stainless steel should have stainless steel should have stainless steel should have stainless and carbon dioxide (essential). Pressure Cell The should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should expressuriation appressure head with the pressurs upply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	single or multiple	
fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models. * The following assemblies should be provided with corresponding utilities: * Pettier Plate Device (0 ° to 180 ° C or better) * Pettier temperature control-enabled plate for heating and cooling of the samples work of the samples work of the samples with measuring plate diameter set. * Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. * Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) * The geometries should have stainless steel hafts which can connect with system. * Pressure Cell Assembly* * It should allow pressurization with air, introgen and carbon dioxide pressurization * pump for nitrogen, air, and carbon dioxide magnetic coupling and contain a pressurization. * The cell should enable pressurization pump for nitrogen, air, and carbon dioxide magnetic coupling and contain a pressurization. * The cell should enable pressurization pump for nitrogen, air, and carbon dioxide pressurization. * The cell should be pressurized should be magnetic coupling and contain a pressure head with a dapters, compatible pressure sensors, and other necessary utilities. * The cell should be preferably made of titanium for anti-corrosion while		
fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Patier Plate Device (0 °C to 180 °C or better) Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder 1 set. Parallel Plate Geometry with measuring plate described of the samples with a screw-on plate holder 1 set. Parallel Geometry with measuring plate described of the samples of th		
fitting facility to classify material behaviour by various rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Patier Plate Device (0 °C to 180 °C or better) Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder 1 set. Parallel Plate Geometry with measuring plate described of the samples with a screw-on plate holder 1 set. Parallel Geometry with measuring plate described of the samples of th	f. Modeling & curve	
classify material behaviour by various rheological models (flow, oscillation & creepl and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 % to 180 % or belier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Plate Geometry with measuring plate diameter (stainless steed) of 50-60mm -1 set. Cone Plate Geometry with measuring cone diameter 2 Softom with 2' angle (stainless steed) -1 set. I set. Cone Plate Geometry with measuring cone diameter 2 Softom with 2' angle (stainless steed) -1 set. I set. Pressure Cell Assembly I set should have stainless steed shafts which can connect with system. Pressure Cell Assembly It should include a hybrid pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide (essential). Phase cell should enable magnetic coupling and contain a pressure head with the pressure surpply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
behaviour by various rheological models (flow, oscillation & creep) and user defined models. * The following assemblies should be provided with corresponding utilities: • Petiter Plate Device (0° C to 180° C or better) • Petiter temperature control-enabled plate for healing and cooling of the samples with a screw on plate in the control of the samples with a screw on plate in ser. • Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. • Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. • The geometries should have stainless steel has should have stainless steel shafts which can connect with system. • Pressure Call Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a bressurization pump for nitrogen, air, and carbon dioxide pressurization pump for nitrogen, air, and carbon dioxide pressurization. • The cell should enable pressure bead with the pressurization valid in a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while		
warious rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: • Politer Plate Device (0 ° to 180 ° to better! • Pelite emperature cological plate of the plat	classify material	
warious rheological models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: • Politer Plate Device (0 ° to 180 ° to better! • Pelite emperature cological plate of the plat	behaviour by	
models (flow, oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 ° C to 180 ° C or better) Petiter temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder—1 set. Periter temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder—1 set. Periter temperature diameter (stainless steel) of 50-60mm = 1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) = 1 set. The geometries should have stainless steel halts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid proper		
oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 °C to 180 °C or better) Petiter temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm -1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2² angle (stainless steel) - 1 set. The geometries should stainless steel) have stainless steel hafts with system. Pressure Pressure Cell Assembly It should allow pressurization with air, mitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable magnetic coupling and contain a pressure land with the pressurs upply sadapters, compatible pressure supply sadapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	_	
oscillation & creep) and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 °C to 180 °C or better) Petiter temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm -1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2² angle (stainless steel) - 1 set. The geometries should stainless steel) have stainless steel hafts with system. Pressure Pressure Cell Assembly It should allow pressurization with air, mitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable magnetic coupling and contain a pressure land with the pressurs upply sadapters, compatible pressure supply sadapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	models (flow,	
and user defined models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 °C to 180 °C or better) Petiter temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder - 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel) have stainless steel halfs which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure halfs which cell should enable magnetic coupling and contain a pressur supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
models. The following assemblies should be provided with corresponding utilities: Petiter Plate Device (0 °C to 180 °C or better) Petitier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm -1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2 stainless steel) -1 set. **The geometries should have stainless steel halts withch can connect with stainless steel shalts withch can connect with the pressurization with air, mitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
• The following assemblies should be provided with corresponding utilities: • Peltier Plate Device (0° C to 180° C or better) • Peltier imperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder – 1 set. • Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60 mm – 1 set. • Cone Plate Geometry with measuring cone diameter 25 mm with 2° angle (stainless steel) – 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization. • The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while	and user defined	
• The following assemblies should be provided with corresponding utilities: • Peltier Plate Device (0° C to 180° C or better) • Peltier imperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder – 1 set. • Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60 mm – 1 set. • Cone Plate Geometry with measuring cone diameter 25 mm with 2° angle (stainless steel) – 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization. • The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while	models.	
should be provided with corresponding utilities: Peltier Plate Device (0° C to 180° C or better) Peltier temperature control-enabled plate for beating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. Come Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable measuring apressurization pump for nitrogen, air, and carbon dioxide (essential). The cell should enable measure supply adapters, compatible pressure supply and of titanium for anti-corrosion while		
should be provided with corresponding utilities: Peltier Plate Device (0° C to 180° C or better) Peltier temperature control-enabled plate for beating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. Come Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable measuring apressurization pump for nitrogen, air, and carbon dioxide (essential). The cell should enable measure supply adapters, compatible pressure supply and of titanium for anti-corrosion while		
should be provided with corresponding utilities: Peltier Plate Device (0° C to 180° C or better) Peltier temperature control-enabled plate for beating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. Come Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The call should enable magnetic coupling and carbon dioxide (essential). The cell should enable magnetic coupling and contain a pressur surject su	 The following assemblies 	
o Pettier Plate Device (0 °C to 180 °C or better) Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder −1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm −1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2* angle (stainless steel) − 1 set. **The geometries should have stainless steel shafts which can connect with system. **Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon (essential) It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization pressurization **The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure supply adapters, compatible pressure sensors, and other necessary utillines. The cell should be preferably made of titanium for anti- corrosion while		
o Peltier Plate Device (0° C to 180° C or better) Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm -1 set. Come Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel shalts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure supply adapters, compatible pressure successors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
o Peltier Plate Device (0° C to 180° C or better) Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder -1 set. Parallel Geometry with measuring plate diameter (stainless steel) of 50-60mm -1 set. Come Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel shalts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure supply adapters, compatible pressure successors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	corresponding utilities:	
O °C to 180 °C or better Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. **The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nilrogen and carbon dioxide (essential). It should include a hybrid pressurization. Pressure arbon dioxide (essential). It should include a hybrid pressurization. **The cell should enable magnetic coupling and contain a pressurization. **The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. **The cell should be preferably made of titanium for anti-corrosion while		
Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder – I set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. **The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly I should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable magnetic coupling and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressurization. The cell should enable magnetic coupling and contain a pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder — I set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm — I set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) — I set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable member of the carbon dioxide pressurization. The cell should enable magnetic coupling and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, companible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	(0 °C to 180 °C or	
Peltier temperature control-enabled plate for heating and cooling of the samples with a screw-on plate holder — I set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm — I set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) — I set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization. The cell should enable member of the carbon dioxide pressurization. The cell should enable magnetic coupling and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, companible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	better)	
control-enabled plate for heating and cooling of the samples with a screw-on plate holder – I set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. **The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly I should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
for heating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. **The geometries should have stainless steel shafts which can connect with system. **Pressure Cell Aassembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
for heating and cooling of the samples with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. **The geometries should have stainless steel shafts which can connect with system. **Pressure Cell Aassembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	control-enabled plate	
cooling of the samples with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel) have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure sensors, and other necessary utilities. The cell should be pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
with a screw-on plate holder – 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm – 1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure sensors, and other necessary utilities. The cell should be pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	cooling of the samples	
holder - 1 set. Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. **Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. **The geometries should have stainless steel shafts which can connect with system. **Pressure Cell Assembly** It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. **Pressure Cell Should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure supply adapters, compatible pressure sensors, and other necessary utilities. **The cell should be preferably made of titanium for anticorrosion while	with a screw-on plate	
Parallel Plate Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. The geometries should have stainless steel hafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while		
Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. • Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization. • The cell should enable magnetic coupling and contain a pressure had with the pressure supply adapters, compatible pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while		
Geometry with measuring plate diameter (stainless steel) of 50-60mm - 1 set. • Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization. • The cell should enable magnetic coupling and contain a pressure had with the pressure supply adapters, compatible pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while	 Parallel Plate 	
measuring plate diameter (stainless steel) of 50-60mm - 1 set. • Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. • The cell should enable magnetic coupling and contain a pressure shead with the pressure surply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while		
diameter (stainless steel) of 50-60mm - 1 set. • Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) - 1 set. • The geometries should have stainless steel shafts which can connect with system. • Pressure Cell Assembly • It should allow pressurization with air, nitrogen and carbon dioxide (essential). • It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. • The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. • The cell should be preferably made of titanium for anti-corrosion while	_ =	
set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	measuring plate	
set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti-corrosion while	diameter (stainless	
set. Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure sure surely adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide epressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	,	
Cone Plate Geometry with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide epressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	set.	
with measuring cone diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
diameter 25mm with 2° angle (stainless steel) – 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	with measuring cone	
angle (stainless steel) - 1 set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. Pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
I set. The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	angle (stainless steel) –	
The geometries should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	1 set.	
should have stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
stainless steel shafts which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	8	
which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	should have	
which can connect with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	stainless steel shafts	
with system. Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	which can connect	
o Pressure Cell Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while	with system.	
Assembly It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
 It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 		
 It should allow pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 	Assembly	
pressurization with air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
air, nitrogen and carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	1	
carbon dioxide (essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	air, nitrogen and	
(essential). It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
 It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 		
 It should include a hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 		
hybrid pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
pressurization pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
pump for nitrogen, air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	pressurization	
air, and carbon dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	grande for situacion	
dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
dioxide pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	air, and carbon	
pressurization. The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while		
 The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 		
 The cell should enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anticorrosion while 	pressurization.	
enable magnetic coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
coupling and contain a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	<u> </u>	
a pressure head with the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	coupling and contain	
the pressure supply adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
adapters, compatible pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while	the pressure supply	
pressure sensors, and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
and other necessary utilities. The cell should be preferably made of titanium for anti- corrosion while		
utilities. The cell should be preferably made of titanium for anticorrosion while		
utilities. The cell should be preferably made of titanium for anticorrosion while	and other necessary	
The cell should be preferably made of titanium for anticorrosion while		
preferably made of titanium for anti-corrosion while		
preferably made of titanium for anti-corrosion while	■ The cell should be	
titanium for anti- corrosion while		
corrosion while		
	corrosion while	
	 	<u>. </u>

	using carbonated		
	fluids.		
	P 11		
	Double gap		
	measuring geometry		
	(made of titanium)		
	for low viscous		
	samples - 1 set.		
	 The assembly should 		
	accompany a		
	temperature control		
	device for electrical		
	heating between 0 °C		
	to 180 °C or better		
	with the necessary		
	utilities and a		
	circulator.		
	A minimum pressure		
	of 150 bar is		
	essential; however, a		
	pressure of up to		
	400 bar or better is		
	desirable with a		
	pressure sensor for a		
	complete range.		
	23. Building Material Cell		
	(BMC)		
	i. The BMC should be		
	able to handle paste-		
	like material with		
	bigger particles (e.g.,		
	cement slurry) and		
	abrasive materials		
	(particle size up to		
	5mm).		
	ii. It should include a		
	suitable sample cup, a		
	stirrer (for abrasive		
	materials), and a cage		
	that prevents slippage		
	of the cup, which		
	should also be easy to		
	clean.		
	iii. The approximate		
	sample volume should		
	be 400ml.		
	iv. The assembly should		
	have an air-cooled		
	Peltier Temperature		
	control (0 °C to 80 °C or		
	better)		
	v. Air dryer and air		
	filtration unit to		
	separate oil, fine		
	particles, etc.		
	F, 300.		
	The system should be		
	upgradable to powder		
	rheology, tribology & humidity		
	attachments		
	The system should be offered		
	with a suitable & branded		
	Windows 10/Macintosh-based		
		Ì	
	or higher operating system-		
	based PC workstation with		
	based PC workstation with licensed Microsoft Office, at		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th generation/AMD Ryzen 5		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th generation/AMD Ryzen 5 processor/ Apple M2 chip with		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th generation/AMD Ryzen 5 processor/ Apple M2 chip with 8-core CPU, high-definition		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th generation/AMD Ryzen 5 processor/ Apple M2 chip with		
	based PC workstation with licensed Microsoft Office, at least Intel i7 11 th generation/AMD Ryzen 5 processor/ Apple M2 chip with 8-core CPU, high-definition		

HDD, 16GB RAM, 27" LED Display, external CD/DVD drive, Bluetooth 5.0 or better, WiFi, 4GB graphics card.	
A branded air conditioner (AC) for standard temperature and humidity control should be provided to ensure better functioning of the equipment.	
The OEM should facilitate on- site installation with training.	
The OEM should provide 3 years on-site warranty with spares with additional 3 years post-warranty Annual Maintenance Support.	

General Requirement	Bidder's Compliance/Deviation
Bidder/supplier shall be responsible for successful onsite installation/commissioning and satisfactory	
demonstration of its features, operation and	
application, routine and preventive maintenance	
aspects of the equipment within thirty (30) days from	
the delivery.	
The vendor must provide at least one day training to users (free of cost).	
DOCUMENTATION: All the documents / manuals and	
certifications to be provided in English.	
Operation and maintenance manual (both hard and soft copies) – 1 No.	
Application software manual (both hard and soft copies) – 1 No.	
Guarantee certificate for the supply of spare parts and	
consumables of the equipment for at least 10 years on	
OEM's letter head.	
The firm must provide a 'Technical Compliance	
Report' against each technical specification.	
All technical details should be supported by	
documentary evidence in form of technical brochures.	

Optional Item:

AMC: AMC for 3 years after the warranty period may be separately quoted, and AMC must include Spares, Consumables, and Service Engineer charges.

Place:					
Date:			Signature	and seal	of the Manufacturer/ Bidder
Technical	Specifications	Compliance	Statement	of	"Automatic Rotational Rheometer
(Research	Grade)" should b	<u>esubmitted as</u>	per format gi	ven in An	nexure - I (On the Company's Letter
<u>Head)</u>					

MANUFACTURERS' AUTHORIZATION FORM (MAF)(ON THE LETTER HEAD OF THE COMPANY)

[NOTE: The Bidder shall require the Manufacturer to fill in this Form in accordance with the instructions indicated. This letter of authorization should be **on the letterhead of the Manufacturer** and should be signed by a person with the proper authority to sign documents that are binding on the Manufacturer. It should be included by the Bidder inits bid]

No. Dated

Date: [insert date (as day, month and year) of Bid Submission]Tender

No.: [insert number from Invitation for Bids]

To,

The Director

Rajiv Gandhi Institute of Petroleum Technology

Mubarakpur, Mukhtia, Bahadurpur

POST: Harbanshganj, Jais, Amethi - 229304

WHEREAS

We [insert complete name of Manufacturer], who are official manufacturers of [insert type of goods manufactured], having factories at [insert full address of Manufacturers factories], do hereby authorize [insert complete name of Bidder] to submit a bid the purpose of which is to provide the following Goods, manufactured by us [insert name and or brief description of the Goods], and to subsequently negotiate and sign the Contract.

We hereby extend our full guarantee and warranty in accordance with the General Conditions of Contract, with respect to the Goods offered by the above firm.

Signed: [insert signature(s) of authorized representative(s) of the Manufacturer] Name: [insert	
complete name(s) of authorized representative(s) of the Manufacturer] Title/Designation: [insert titl	e]
Duly authorized to sign this Authorization on behalf of: [insert complete name ofBidder]	

Dated on	day of,	,	[insert date of signing]
Yours faithfu	ılly,		
(Name of ma	nufacturers)		

OR

SELF DECLARATION OF MANUFACTURING UNIT

PRICE REASONABILITY CERTIFICATE

(ON THE LETTER HEAD OF THE COMPANY)

ACA simi stag ther actio	DEMI lar su e it ha i in su	C and RESE pplies made s been found ich condition inst the tend	CARCH Insti in recent p I that the qu RGIPT, Am	the Dated dated tutions and are ast. If they have oted rates are hi ethi, will have the	d not mo been a gher tha	re than as opproved by the nthe rates a	the items are excluse tharged to other Director pplicable to	vide our bi vively for other Govt., r, RGIPT an supply to G	id No. supply to /PSU"s for d if at any overnment
(Nar	ne of r	nanufacture	rs)						
(Sign	nature	with date) (Name						
and	design	nation)							
Duly	y auth	orized to sign	n tender for	and on behalf of					

DECLARATION (ACCEPTANCE OF TERMS & CONDITIONS)(ON THE LETTER HEAD OF THE COMPANY)

Paı	I,Son/Daughter of Shritner/CEO/MD/Director/Authorized Signatory of M/ssign this tender document.	
2.	I have carefully read and understood all the terms and omy acceptance of the same.	conditions of the tender and hereby convey
3.	The information/ documents furnished along with the at the best of my knowledge and belief.	bove application are true and authentic to
4.	I/ we/ am are well aware of the fact that furnishing of a would lead to rejection of my tender at any stage bes appropriate law.	,
5.	Each page of the tender document and papers submitted and signed, and I take full responsibility for the entire do	
Da	te:	
Pla	ce:	Signature of the Authorized Person
		Full Name:
		Company Seal:

DECLARATION SHEET

We,	hereby certify that all the information and datafurnished
by our organization with regard to	this tender specification are true and complete to the best of our
knowledge. I have gone through the	e specification, conditions and stipulations in details and agree to
comply with the requirements and in	ntent of specification.

This is certified that our organization has been authorized (Copy attached) by the OEM to participate in Tender. We further certified that our organization meets all the conditions of eligibility criteria laid down in this tender document. Moreover, OEM has agreed to support on regular basis with technology / product updates and extend support for the warranty.

The prices quoted in the financial bids are subsidized due to academic discount given to RGIPT, Jais, Amethi.

We, further specifically certify that our organization has not been Black- Listed/ De Listed or put to any Holiday by any Institutional Agency/ Govt. Department/ Public Sector Undertaking in the last three years.	
1. Phone	
2. Fax	
3. E-mail	
4. Contact Person Name	
5. Mobile Number	
6. TIN Number	
7. PAN Number	
8. (In case of on-line payment of TenderFees) UTR No. (For Tender Fee)	
9. (In case of on-line payment of EMD)UTR No. (For EMD)	
10. Kindly provide bank details of thebidder in the following format:a) Name of the Bank	
b) Account Number	
c) Kindly attach scanned copy of one Cheque book page to enable us to return the EMD to unsuccessful bidder	

(Signature of the Tenderer) Name:

Seal of the Company

NON-BLACKLISTING DECLARATION

It has been certified that all information provided in tender form is true and correct to the best of my knowledge and belief. No forged / tampered document(s) are produced with tender form for gaining unlawful advantage. We understand that RGIPT, Amethi is authorized to make enquiry to establish the facts claimed and obtain confidential reports from clients.

In case it is established that any information provided by us is false / misleading or in the circumstances where it is found that we have made any wrong claims, we are liable for forfeiture of EMD and or any penal action and other damages including withdrawal of all work/purchase orders being executed by us. Further RGIPT, Amethi is also authorized to blacklist our firm/company/agency and debar us in participating in any tender/bid in future.

I / We assure the Institute that neither I / We nor any of my / our workers will do anyact/s which is improper / illegal during the execution in case the tender is awarded to us.

Neither I/We nor anybody on my/our behalf will indulge in any corrupt activities/practices in my/our dealing with the Institute.

Our Firm/Company/Agency is not been blacklisted or banned by any Central Government Department/ State Government Department, PSU, University, Autonomous Institute or Any other Govt. Organization.

Date Signature of the Tenderer Place Stamp

Note: This certificate should be executed on duly notarized `100/- Non JudicialStamp Paper.

List of Govt. Organization/Department/Institutes

undertaken such work during last three years (must be supported with work orders)							
Name of the Organization	Name of Contact Person	Contact No.					
	(Signature of the	Tenderer)					
	Name:						

Seal of the Company

<u>FINANCIAL BID - Supply & Installation of 01 no.</u> Automatic Rotational Rheometer (Research Grade)

(To be filled in BoQ Format on CPP Portal)

<u>Financial Bid in Indian Currency (For indigenous/Imported equipment)</u>:

 Name of the

Bidder/Tenderer: Name & Model No of offered goods:

Tender No.:

S1. No.	Details	Total Amount (In INR)
1	Basic Cost of "Automatic Rotational Rheometer (Research Grade)"	
	defined inTechnical Specifications Statement of the Tender	
2	Comprehensive Cost of Warranty	
3	Add: Packing & Forwarding Charges, If any	
4	Add: Installation & Commissioning Charges, if any	
5	Add: Transportation Charges up to RGIPT, Jais, Amethi, ifany	
6	Add: GST (Taxes)	
Tota	l Price (Sum of Sl. No 1 to 6) F.O.R RGIPT, Jais, Amethi Price	

II. For Local Supplies -

S1.	Sl. Details						
No.		Amount (In INR)					
1	Cost of Local Supplies defined in Technical SpecificationsStatement of the Tender Document (Please mention the items)						
2	Add: Packing & Forwarding Charges, If any						
3	Add: Installation & Commissioning Charges, if any						
4	Add: Transportation Charges up to RGIPT, Jais, Amethi, ifany						
5	Add: Cost of Warranty						
6	Add: GST (Taxes)						
Tota	Price (Sum of Sl. No 1 to 6) F.O.R RGIPT, Jais, AmethiPrice						

Note: The Institute will provide DSIR & GST Exemption Certificate.

I.							\ I I			accessories):
II.	Total	Bid pı	rice in I	ndia	n curren	cy (Local Su	pplies):			
In wo		•••••	•••••	•••••	•••••					
b) Ti	ne cost c	of option	onal ite	ms s	hall be ir	ndicated sep	parately			
Date								Sig	gnature	e of the Tenderer
Place							Sta	amp		

A. Financial Bid in Foreign Currency:

Price Schedule Form: Price schedule for goods being offered from abroad
In currency other than INR (Indian Rupees)
(Separate form to be used for each item offered)
(ON THE LETTER HEAD OF THE COMPANY)

I. Name of the Bidder/Tenderer:

Name & Model No of offered goods:

Tender No.:

(Sepa:	rate Prices should be defined for each instrument)	
No.	Details (Basic Cost of Equipment with accessories)	ce per unit in (-
)
A.	Country of origin	
	Payment in Foreign Currency	
1	FOB (named port of shipment)-Ex-Works Price	
2	Freight and Insurance up to Indian Airport/port	
3	Total Price at Indian Airport /port (CIP/CIF) (1+2)	
В.	Reimbursement of Expenses (in Indian Rupees)	
4	**Custom Duty against DSIR certificate (Please mentioned % also)	
5	Custom clearance and other charges, if any (with breakup)	
6	Inland Charges for Insurance & transportation to RGIPT Jais, Amethi	
7	Installation, commissioning and training Charges, if any	
8	Cost of Comprehensive Warranty	
	Total Price F.O.R RGIPT, Jais, Amethi Price	
	(A + B) (Sum of Sl. No 1 to 8)	

** RGIPT, Jais, Amethi have Custom/Excise Exemption Certificate.

For Local Supplies -

No.	Details	tal Amount (In INR)
1	Cost of Local Supplies defined in Technical Specifications Statement of the Tender Document (Please mention the items)	
2	Add: Packing & Forwarding Charges, If any	
3	Add: Installation & Commissioning Charges, if any	
4	Add: Transportation Charges up to RGIPT, Jais, Amethi, if any	
5	Add: Cost of Warranty	
6	Add: GST (Taxes)	
	Total Price (Sum of Sl. No 1 to 6) F.O.R RGIPT, Jais, Amethi Price	

I.	Total Bid price in Foreign Currency (Equipment Cost with accessories):	
II.	Total Bid price in Indian currency (Local Supplies):	••

Optional Item:

AMC for 3 years after the warranty period may be separately quoted and AMC must include Spares, Consumables and Service Engineer charges.

THE BIDDER MAY ADD ROWS AS PER REQUIREMENT TO INCLUDE THE PRICES OF ALL COMPONENTS/ PARTS, WARRANTIES, INSTALLATION ETC. WHICHEVER APPLICABLE.

- a) Indian Agents Name & Address
- b) The cost of optional items shall be indicated separately
- c) In case the price quoted in Foreign Currency (Other than INR), for the purpose of comparison the Exchange Rate prevailing on the date of opening of Financial Bid will be considered.

Date	Signature of the Tenderer
Place	Stamp